



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/033,642	01/03/2002	Hong Kui Yang	01-766 72202 (6653)	9246
7	590 08/16/2004		EXAMI	NER
DUANE MORRIS, LLP ONE MARKET, SPEAR TOWER, SUITE 2000 SAN FRANCISCO, CA 94105-1104			CHOW, CHARLES CHIANG	
			ART UNIT	PAPER NUMBER
			2685	
			DATE MAILED: 08/16/2004	4

Please find below and/or attached an Office communication concerning this application or proceeding.

,					
	Application No.	Applicant(s)			
	10/033,642	YANG ET AL.			
Office Action Summary	Examiner	Art Unit			
	Charles Chow	2685			
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the	correspondence address			
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be till y within the statutory minimum of thirty (30) day will apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	mely filed ys will be considered timely. In the mailing date of this communication. ED (35 U.S.C. § 133).			
Status					
1) Responsive to communication(s) filed on <u>04 D</u>	ecember 2003.				
,					
3) Since this application is in condition for allowar	· · · · · · · · · · · · · · · · · · ·				
Disposition of Claims					
4) ☐ Claim(s) 1-11 is/are pending in the application. 4a) Of the above claim(s) is/are withdraw 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or	wn from consideration.				
Application Papers					
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 03 January 2002 is/are: Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Ex	a)⊠ accepted or b)⊡ objected drawing(s) be held in abeyance. Se ion is required if the drawing(s) is ob	e 37 CFR 1.85(a). ojected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority document: 2. Certified copies of the priority document: 3. Copies of the certified copies of the priority application from the International Bureau * See the attached detailed Office action for a list	s have been received. s have been received in Applicat rity documents have been receiv u (PCT Rule 17.2(a)).	ion No ed in this National Stage			
Attachment(s)	»□				
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date 	4)	r (PTO-413) ate Patent Application (PTO-152)			

Art Unit: 2685

Detailed Action

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 1. Claims 1, 6, 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Aschwanden (US 5,896,306) in view of Peterzell (US 2002/0123,319 A1).

Regarding claim 1, Aschwanden teaches a direct conversion receiver DCR (Fig. 1) comprising a pair of quadrature conversion path (channel A, channel B in Fig. 1) each of said quadrature conversion paths receiving an RF input signal (the signal from antenna to RF processor) and converting said RF signal to a digital base band signal (the converted base band signal is of 2.86 MHz wide for low-pass-filter LPF having cut off of 2.86 MHz in col. 3, line 57 to col. 4, line 4; the base band signal to I-processor, Q-processor in Fig. 1, col. 6, lines 7-11), each quadrature comprising a mixer mixing RF input signal with a carrier phase signal (mixer MA, MB, mixing rf signal from rf processor with carrier phase signals sinw₀, consw₀, in Fig. 1), an analog filter receiving a quadrature base band signal from said multiplied and providing a filtered base band signal (the LPF-A, LPF-B in Fig. 1 for providing filtered base band signal with cut off of 2,86 MHz having sharp stop band attenuation, col. 3, lines 57 to col. 4, lines 4; col. 2, line 62 to col. 3, line 7), an analog-to-digital converter ADC converting a quadrature baseband component to a digital band signal (the analog to digital converter ADC-A, ADC-B, converts signal from low pass filter LPF-A,

Art Unit: 2685

LPF-B, to data stream, col. 3, lines 30-34), a phase equalizer compensating for phase distortion arising in the analog filter (the phase corrector-A, phase corrector-B, cancels the distorted phase response of the group delay of the low pass filter LPF-A/LPF-B, due to the sharp cut off of the frequency response of the low pass filter LPF, col. 3, lines 34-45; col. 3, lines 7-23), the base band processor receive quadrature digital base band outputs from the pair of quadrature conversion paths and providing information therefrom (the I-processor, Qprocessor for receiving corrected in-phase I, quadrature phase Q base band signal for providing demodulated data, Fig. 1). Aschwanden fails to teach a 5th order elliptical filter filtering said quadrature base band component. However, Peterzell teaches the 5th order elliptic filter filtering said quadrature base band component (IIR filter 910 is a fifth order digital filter for rejecting jammers in the digital base band signal, Fig. 8, [0089]) of the direct conversion receiver 800 (Fig. 8, abstract, [0002, 0037]). Peterzell teaches an improved technique for reducing the jammer interference [0033-0037] by including the 5th order elliptic filter. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to modify Aschwanden with Peterzell's 5th elliptical filter, such that the interference signal could be reduced.

Regarding claim 6, Aschwanden teaches a direct conversion receiver DCR (Fig. 1) comprising a pair of quadrature conversion path (channel A, channel B in Fig. 1) each of said quadrature conversion paths receiving an RF input signal (the signal from antenna to RF processor) and converting said RF signal to a digital base band signal (the converted base band signal is of 2.86 MHz wide for low-pass-filter LPF having cut off of 2.86 MHz in col. 3, line 57 to col. 4, line 4; the base band signal to I-processor, Q-processor in Fig. 1, col. 6,

Art Unit: 2685

lines 7-11), each quadrature comprising a mixer mixing RF input signal with a carrier phase signal (mixer MA, MB, mixing rf signal from rf processor with carrier phase signals sinw_o, conswo, in Fig. 1), an analog filter receiving a quadrature base band signal from said multiplied and providing a filtered base band signal (the LPF-A, LPF-B in Fig. 1 for providing filtered base band signal with cut off of 2,86 MHz having sharp stop band attenuation, col. 3, lines 57 to col. 4, lines 4; col. 2, line 62 to col. 3, line 7), an analog-todigital converter ADC converting a quadrature baseband component to a digital band signal (the analog to digital converter ADC-A, ADC-B, converts signal from low pass filter LPF-A, LPF-B, to data stream, col. 3, lines 30-34), a phase equalizer compensating for phase distortion arising in the analog filter (the phase corrector-A, phase corrector-B, cancels the distorted phase response of the group delay of the low pass filter LPF-A/LPF-B, due to the sharp cut off of the frequency response of the low pass filter LPF, col. 3, lines 34-45; col. 3, lines 7-23), the base band processor receive quadrature digital base band outputs from the pair of quadrature conversion paths and providing information therefrom (the I-processor, Qprocessor for receiving corrected in-phase I, quadrature phase Q base band signal for providing demodulated data, Fig. 1). Aschwanden fails to teach a 5th order elliptical filter receiving said quadrature base band component and providing a filtered digital base band component. However, Peterzell teaches the a 5th order elliptical filter receiving said quadrature base band component and providing a filtered digital base band component (IIR filter 910 is a fifth order digital filter for rejecting jammers in the digital base band signal, Fig. 8, [0089]) of the direct conversion receiver 800 (Fig. 8, abstract, [0002, 0037]). Peterzell teaches an improved technique for reducing the jammer interference [0033-0037] by

Art Unit: 2685

including the 5th order elliptic filter. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to modify Aschwanden with Peterzell's 5th elliptical filter, such that the interference signal could be reduced.

Regarding claim 9, Aschwanden teaches a direct conversion receiver DCR (Fig. 1) comprising a pair of quadrature conversion path (channel A, channel B in Fig. 1) each of said quadrature conversion paths receiving an RF input signal (the signal from antenna to RF processor) and converting said RF signal to a digital base band signal (the converted base band signal is of 2.86 MHz wide for low-pass-filter LPF having cut off of 2.86 MHz in col. 3, line 57 to col. 4, line 4; the base band signal to I-processor, Q-processor in Fig. 1, col. 6, lines 7-11), each quadrature comprising a mixer mixing RF input signal with a carrier phase signal (mixer MA, MB, mixing rf signal from rf processor with carrier phase signals sinw_o, consw_o, in Fig. 1), an analog filter receiving a quadrature base band signal from said multiplied and providing a filtered base band signal (the LPF-A, LPF-B in Fig. 1 for providing filtered base band signal with cut off of 2,86 MHz having sharp stop band attenuation, col. 3, lines 57 to col. 4, lines 4; col. 2, line 62 to col. 3, line 7), an analog-todigital converter ADC converting a quadrature baseband component to a digital band signal (the analog to digital converter ADC-A, ADC-B, converts signal from low pass filter LPF-A, LPF-B, to data stream, col. 3, lines 30-34), a phase equalizer compensating for phase distortion arising in the analog filter (the phase corrector-A, phase corrector-B, cancels the distorted phase response of the group delay of the low pass filter LPF-A/LPF-B, due to the sharp cut off of the frequency response of the low pass filter LPF, col. 3, lines 34-45; col. 3, lines 7-23), the base band processor receive quadrature digital base band outputs from the

Art Unit: 2685

pair of quadrature conversion paths and providing information therefrom (the I-processor, Q-processor for receiving corrected in-phase I, quadrature phase Q base band signal for providing demodulated data, Fig. 1). Aschwanden fails to teach a 5th order elliptical filter filtering said quadrature base band signal and providing a quadrature base band component. However, Peterzell teaches a 5th order elliptical filter filtering said quadrature base band signal and providing a quadrature base band component (IIR filter 910 is a fifth order elliptic digital filter for rejecting jammers in the digital base band signal, Fig. 8, [0089]) of the direct conversion receiver 800 (Fig. 8, abstract, [0002, 0037]). Peterzell teaches an improved technique for reducing the jammer interference [0033-0037] by including the 5th order elliptic filter. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to modify Aschwanden with Peterzell's 5th elliptical filter, such that the interference signal could be reduced.

Claims 2-5, 7-8, 10-11 are rejected under 35 U.S.C. 103(a) as being unpatentable over
 Aschwanden in view of Peterzell, as applied to claim 1 above, and further in view of Choi et
 al. (US 2003/0214,926 A1).

Regarding **claim 2**, Aschwanden and Peterzell fail to teach the second order all pass digital phase equalizer. Choi teaches the phase equalizer 205 having the second order all pass transfer function in equation (1) to equation (4), for the all pass digital phase equalizer [0079-0086]. Choi teaches an improved technique for reducing interference from other mobile station's pilot signal, by utilizing digital phase equalizer [0014-0018]. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to modify

Art Unit: 2685

Aschwanden, Peterzell, with Choi's second order all pass digital phase equalizer, such that the interference from other mobile station could be reduced.

Regarding claims 3,8, 11, Choi taught the phase equalizer has transfer function defined by equation (4) in [0084-0085].

Regarding **claim 4**, Peterzell taught each 5th order elliptical filter receives the digital output of the ADC and provides said digital base band component to the phase equalizer (the ADC 880 is connected to IIR filter 910 which is a fifth order elliptic digital filter for rejecting jammers in the digital base band signal, Fig. 8, [0089]).

Regarding **claim 5**, Aschwanden taught each 5th order elliptical filter receives the filtered base band signal from the analog filter (LPF A, LPF B, are seven-pole elliptical LC filters, col. 3, line 57 to col. 4, line 4) and provides the quadrature base band component to the ADC (LPF A, LPF B, is connected respectively to ADC-A, ADC-B), the ADC output being provided to the phase equalizer (the phase correction A, phase correction B, Fig. 1).

Regarding **claims 7**, **10**, Choi taught the second order all pass digital phase equalizer (the phase equalizer 205 having the second order all pass transfer function in equation (1) to equation (4), for the all pass digital phase equalizer [0079-0086]).

Conclusion

- The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.
 - A. US (5,828,955) Lipowski et al. teaches a near direct conversion receiver having the DPS 40 for adjusting, correcting, amplitude, phase error by equalizing the amplitude, phase of the quadrature signal (Fig. 2, abstract).

Art Unit: 2685

4. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Charles Chow whose telephone number is (703)-306-5615.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Edward Urban, can be reached at (703)-305-4385.

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks

Washington, D.C. 20231

or faxed to: (703) 872-9306 (for Technology Center 2600 only)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington, VA, Sixth Floor (Receptionist).

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Technology Center 2600 Customer Service Office whose telephone number is (703) 306-0377.

Charles Chow C.C.

August 2, 2004.

Same a property of